



	<b>NXV560A</b>	<b>NXV1020A</b>	<b>NXV1020AM</b>	<b>NXV1380A</b>	<b>NXV1680A</b>	<b>NXV1680B</b>
Table Size	700 x 420 mm 27.6" x 16.5"	1,120 x 520 mm 44.1" x 20.5"		1,430 x 760 mm 56.3" x 29.9"	1,730 x 760 mm 68.1" x 29.9"	1,730 x 860 mm 68.1" x 33.9"
X-axis Travel	560 mm 22.0"	1,020 mm 40.2"		1,330 mm 52.4"	1,630 mm 64.2"	1,630 mm 64.2"
Y-axis Travel	410 mm 16.1"	520 mm 20.5"		762 mm 30"	762mm 30"	860 mm 33.9"
Z-axis Travel	450 mm 17.7"	540 mm 21.3"		700 mm 27.6"	700mm 27.6"	762 mm 30"
Spindle Speed	12,000 rpm (15,000 rpm)	12,000 rpm (15,000 rpm)				6,000 rpm (10,000 rpm)
Spindle Taper	BBT40					BT50 (BBT50)
Max. Spindle Power (opt.)	18.5 kW (18.5 kW) 25 HP (25 HP)	18.5 kW (18.5 kW) 25 HP (25 HP)		18.5 kW (30 kW) 25 HP (40 HP)	18.5 kW (22 kW) 25 HP (30 HP)	
Tool Magazine Capacity (opt.)	20T	24T (30 / 40 / 60T)		24T (30T)		32T (40T)
Machine Weight	3,000 kg 6,614 lb	5,350 kg 11,795 lb		10,500 kg	11,000 kg	15,500 kg 34,171 lb

1. The manufacturer reserves the right to modify the design, specifications, mechanisms, etc. to improve the performance of the machine without notice.  
All the specifications shown above are just for reference.
2. The appearance of the machines will be diverse due to different model and selectivity of accessories.